



5-1/2" VEKTOR SPECIFICATIONS



TYPICAL TESTED PERFORMANCE TORQUE (44VT.22.03.33.01)					TYPICAL TESTED PERFORMANCE RPM (44VT.22.03.33.01)				
Pressure	Speed 1	Speed 2	Speed 3	Speed 4	GPM	Speed 1	Speed 2	Speed 3	Speed 4
PSI	ft-lb	ft-lb	ft-lb	ft-lb	10	2	4	9	18
1000	9080	4520	1760	880	20	4	8	21	42
2000	18160	9040	3520	1760	40	9	18	45	91
2250	20430	10170	3960	1980	60	14	27	70	139
2500	22700	11300	4400	2200	<p><i>Disclaimer: Technical Values are +/- 5% of Listed Values</i> <i>Speed 1 = Low (Hydraulic) / Low (Mechanical)</i> <i>Speed 2 = High / Low</i> <i>Speed 3 = Low / High</i> <i>Speed 4 = High / High</i></p>				

5-1/2" VEKTOR Tong	Stand Alone	With Backup
Capacity	2-3/8" - 5-1/2" (Tong)	2-3/8" - 6-1/4" (Backup)
Width	31.0" (78.7 cm)	35" (88.9 cm)
Length	51.5" (130.8 cm)	58.5" (148.6 cm)
Height	48.5" (123.2 cm)	79" (200.7 cm)
Weight (lb)	1530 (694 kg)	2970 (1347 kg)
Hyd. System Rated Pressure	2500 psi	
Rated Torque	22,000 ft-lbs (29828 Nm)	
Handle Length	28.5" (Tong)	33.5" (Backup)



Starr Power Tongs, LLC.
 2801 Youngsville Hwy
 Youngsville, LA 70592
 United States of America
 Phone: +1-337-330-2631